

GEKO 9001 E-S/SEBA

Order number : V5048

El. capacity 1 ~ : 9,2 kVA = 7,36kW Steady state
 Power factor : $\cos \varphi = 0,8$
 Voltage 1 ~ : 230V
 Max. sum. current 1 ~ : 40 A
 Current 1~(CEE) : 40 A.
 Current 1~(Schuko) : 16 A
 Max. starting current
 Cos φ 0,6 1 ~ : 60 A
 Frequency : 50 Hz
 Noise pressure (10m Distance) : 70 dB(A)
 Length x Width x Height : 790mm x 550mm x 650mm
 Weight : 138 kg



Engine
 Producer : Briggs & Stratton
 Type : 380447 (Petrol)
 Operating mode : 4-Stroke, 3000 ¹/min / 1800 ¹/min
 Number of cylinders : 2
 Fuel consumption by
 25% / 50% / 75% / 100% load : 2,54l/h / 3,36l/h / 4,46l/h / 5,52l/h
 Cooling system : Air
 Engine power : 12,1 kW
 Start system : Electro start

Generator
 Type : Synchronous
 Cooling System : Air
 Safety class : IP 54

Filling quantity
 Engine oil : 1,7 Litre
 Fuel tank : 10 Litre

Control panel and connections

- 1 x Recoil hand starter
- 2 x Plug socket 1~ 230V/16A (Schuko)
- 1 x Plug socket 1~ 230V/63A (CEE)
- 1 x Operating time counter